

Pre-Installation Fitting Inspection

Pre-Installation Fitting Inspection

- ✓ Ensure the panel is in the upright position- ***DO NOT LAY THE PANEL ON ITS SIDE OR FACE DOWN.**
- ✓ On arrival, check all panels for any visible damage that may have occurred during the shipping process; this must be within three (3) days of delivery to validate Lifetime Warranty.
- ✓ Ensure the panel is the correct size as indicated on the shipping label and your invoice/records.
- ✓ *Carry the unit in an upright position.
- ✓ Check to see if any damages or non-acceptable imperfections are on the panel.
- ✓ Ensure the handle mechanism is functioning correctly. Test by standing the panel in the upright position (handle at the bottom) and operate handle mechanism. **DO NOT install if handle mechanism is not functioning properly**; if there are any imperfections, please contact us immediately.

*May void Lifetime Warranty.

**⚠ WARNING: If panel is installed prior to Pre-Installation Fitting Inspection, ⚠
Lifetime Warranty will be null and void.**



Installation - Basic Stops

Basic Stops Instructions

Openings/Frames Checklist

- ✓ For all basic stops, we recommend the opening to be 1/8inch overall larger than the panel as it should NOT be a tight fit. For all other frames, this is dependent on the frame that is supplied.
- ✓ Ensure the opening is squared.
- ✓ VISTAMATIC® recommends a 5/8inch stop, as a minimum, to cover all spacers and sealants, on all products.
- ✓ There is a 1 inch clearance from the bottom of the glass to the bottom of the handle.

Installation Instructions

1. For basic stops, fix one side of the opening. This can be achieved by screwing/nailing or silicone whichever is suitable for the project. Fit intumescent material, if required, for fire-rated door or any other glazing tape you see fit (our products do not require tape).
2. Place the panel into the opening, if required, use packing wedges to make sure that the panel is sitting square in the opening.
3. Fix the hardwood fixing beads to the reverse side of the opening as described in Part 1. Fix the fixing beads top and bottom, first, and check that the VISTAMATIC® Vision Panel is functioning correctly and the fixing beads are not too tight. **It is VERY IMPORTANT that you DO NOT pinch the panel, as this will stop the VISTAMATIC® Vision Panel from functioning and will void the warranty.** When you are sure that all is correct, fit the side fixing beads the same way.



Installation - Other

Instructions for Hollow Metal Frames/Borrowed Light
Supplied by VISTAMATIC®

Note: For Hollow Metal Frame/Borrowed Light fitting, please follow instructions supplied from the manufacturer, as they vary from each source.

Openings/Frames Checklist

- ✓ For our frames, we recommend the opening to be 1 inch overall larger than the panel ordered. For all other frames, this is dependent on the frame supplier.
- ✓ There is a 1 inch clearance from the bottom of the glass to the bottom of the handle.
- ✓ Make sure the opening is squared.

Installation Instructions

1. Push the frame into one side of the opening (non-screw side). Fit intumescent material, if required for fire rated door, or glazing tape depending on your preference.
2. Carefully place the VISTAMATIC® Vision Panel into the opening.
3. Fit other side of the frame to the other side and then fix screws on top and bottom, first and check that the VISTAMATIC® Vision Panel is functioning correctly, ensuring these are not too tight. **It is VERY IMPORTANT that you DO NOT pinch the panel, as this will stop the VISTAMATIC® Vision Panel from functioning and will void the warranty.** When you are sure that all is correct, fit the side screws in the same way and check again.



Care & Cleaning Guidelines

Care & Cleaning Guidelines

DOs

- ✓ Clean with non-abrasive glass cleaners, mild soaps or detergents diluted with water to clean the glass.
- ✓ Clean using a soft cloth or synthetic window leather.
- ✓ Use a squeegee or soft cloth for drying glass.

DO NOTs

- ✗ Do not use brushes or cleaning tools with sharp edges anywhere on the Vision Panel(s).
- ✗ Do not lay on side or face down, always keep in upright position.